
RODENSTOCK Instruments







The Rodachart 422: Focus on the essentials



What are your benefits?



Precise refraction

Bright and clear chart projection



Cost reduction

maintenance-free LED light source saves costs



Saves time

Gain efficiency due to the smart selection of essential charts



Connectivity

Ready for connection to our Phoromat 2000



Convenient

focus adjustment by rotary aperture

Profit from proven technology.

Rodachart 422 combines efficiency with effectivity by providing a smart selection of the most essential refraction tests.

Excellent features

Plenty of choices

Variety of 42 charts



Bright illumination

White LED light

Light weight

Compact design with 3.6 kg

Fast handling

0.3 sec of chart rotation speed

Convenient function

Rotary aperture for focus adjustment




Chart overview of Rodachart 422





Specifications

MEASUREMENT	
Number of charts	42 charts
Distance of projection	2.5 – 8 m (8 m distance projection screen is optional)
Chart magnification	30 × (When projected at 5 m distance)
Light source	LED Lamp
Connector	RS-232C
Chart rotation speed	Average 0.3 sec
Power save	11 minutes (after last signal)
Tilt angle	± 20 degrees
Resolution	50 lines/mm
Program	2 programs with a maximum of 40 charts each
Power supply	100 – 240 V, 50/60 Hz
Power consumption	25 – 35 VA

DIMENSIONS	
Body (Stand except) WDH	200 × 290 × 172 mm
Body (Stand included) WDH	200 × 290 × 235 mm
Remote control WDH	64 × 196 × 20 mm
WEIGHT	
Stand included	3.6 kg
Remote control	160 g (Battery included)

RODENSTOCK Instruments

Wiesbadener Strasse 21 90427 Nürnberg, Germany Phone +49 (0)911 938 546 2777 Fax +49 (0)911 938 546 220 info@rodenstock-instruments.de www.rodenstock-instruments.de

Rodenstock Instruments is a business unit of Tomey GmbH



Optional equipment

Take a look at the supplementary products in detail. For technical data, please contact us.



